

Technical Data Sheet

Deluxe Cork Floors

531 Listo ready-to-lay cork

Ready-to-lay cork



Article number(s):	FK01 FK02 FK08 FK51
	FK52 FK53 FK55 FK56
	FK57 FK58 FK74
	FK75 FK76 FK78

Material / Construction

Construction of an element	Surface layer: cork
	Middle layer: HDF
	Backing: cork underlay
Surface treatment	Velvet matt varnished
Connection system	DuoConnect laying system
Laying options	Floating installation

E & OE. Subject to change without notice. All previous data sheets are superseded by this issue.

07 | 2019

W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | D-34134 Kassel | info@joka.de | www.joka.de
INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | A-2355 Wiener Neudorf | info@inku.at | www.inku.at

JOKA[®]
Natürlich schöne Räume



Technical Data Sheet

Deluxe Cork Floors

531 Listo ready-to-lay cork

Dimensions and tolerances in accordance with EN 14085. Dimensional characteristics and permitted dimensional deviations, which have been determined in the factory, have been given in accordance with the standard for loose lay floor panels.

Dimensions of the individual element

Dimension	Tolerances
Thickness: 10.5 mm	
Length: 905.0 mm	
Width: 295.0 mm	
Permitted width deviation of the top layer	$\leq \pm 0.10\%$ max. 0.5 mm
Permitted deviation of the squareness	≤ 0.2 mm
Permitted length deviation of the surface layer	$\leq \pm 0.10\%$ max. 2.0 mm
Permitted deviation of the element thickness	$\leq \pm 0.30$ mm
Height difference between joined elements	≤ 0.20 mm
Joint opening between joined elements	≤ 0.20 mm
Straightness of the surface layer	≤ 0.30 mm
Flatness of the element (concave / convex width (cup))	$\leq 0.10\%$ / $\leq 0.15\%$
Flatness of the element (concave / convex length (bow))	$\leq 0.50\%$ / $\leq 1.0\%$

Product characteristic

Use class	23 / 31
Reaction to fire	E _{fl} s1
Impact sound insulation	16 dB (Δ L _w)
Weight per unit area	8000 g/m ² ($\pm 10\%$)
Effect of a furniture leg	no visible changes
Effect of a castor chair	no visible changes with chair castor type W
Electrostatic behaviour	not antistatic
Residual indentation	≤ 0.40 mm
Slip resistance	DS
Formaldehyde emission	E1
Thermal resistance	≤ 0.15 (m ² x K) /W suitable for hot water underfloor heating
Pentachlorophenol (PCP) content	PCP free

Technical Data Sheet

Deluxe Cork Floors

531 Listo ready-to-lay cork

Packaging

Contents (area) per pack	2.14 m ²
Contents per pallet	111.07 m ²
Number of elements per pack	8
Packs per pallet	52

General product data

Declaration of performance	PAR1801601
----------------------------	------------

Note

Cork is a natural product and its colour and texture can therefore differ. Samples, brochures and photos are therefore only approximate and are not binding. The action of sunlight also influences the natural change in colour. As a result, the product at the time of delivery can have clear differences to the sample provided.

